



- 42 meter (138 ft.) Vertical reach
- 165 m³/hr concrete delivery rate
- 1268 psi (87.5 Bar) Concrete Pressure
- 5" (125mm) Concrete Line

Boom: Radiused boom design makes it more flexible and compact. High strength alloy steel base frame and boom makes it rugged and durable.

Pedestal: XXT Boom Pedestal designed with a common pin outrigger support minimizes boom bounce and eliminates pedestal torsion. Heavy duty bearings rotate the delivery boom smoothly through a 370 degree slewing range.

Outriggers: "XXT" Outriggers can be positioned to give upto 70 percent additional working range in confined work-sites. Outrigger controls located at the truck boom base. Unsurpassed stability while pumping.

Delivery Line: 5" delivery line with durable pipe sections are bracket mounted for easy delivery line maintenance. Use of standard 90 degree elbows reduce spare part inventory.

Wash Out & Blow out: Air compressor connected to blowout system, purges the concrete at the end of the job. High pressure water blaster makes clean-out quick.

- 4 Section Roll & Fold reduces outlay
- "XXT" Outrigger and Boom Pedestal
- Super Efficient Hydraulic System.
- Designed and made in Australia.

Concrete Pump: Super Efficient Semi-Closed Loop Hydraulic System with multiple hydraulic pumps making it the most fuel efficient pump in the market. Electronic flow control enables fine control of concrete flow and gives you the option of a Soft Push mode, minimizing pipe movement when pumping over post stress cables or formwork.. "HYPERCHROME" Chrome Carbide wear plate and wear rings, gives long life with economical replacement cost. (Tungsten Carbide option available)

Longer Pump Stroke: **2400mm (93.5")** Concrete Cylinder giving smoother pumping action and longer pump parts life. Piston-side setup of main rams delivers higher concrete cylinder output pressures, with lower hydraulic ram pressures.

Large Volume Hopper with Remixer: Large volume Hopper with hydraulic remixer ensures efficient filling of the concrete cylinders., 8" X 7" S - Tube is standard.

Remote Controls: Cordless remote control and backup 35m cable remote.